


This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

BEARINGS AND TOOLS COVERED

BEARING #	TOOL #
406-310-403-101	RBSC7008-P
206-010-470-101	RBSC7028-P
406-312-100-101	RBSC7048-P
412-010-182-103	RBSC7188-P

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1		CHANGED TOOL # RBSC412-010-103-P TO RBSC7188-P TO CLARIFY TOOLING IDENTIFICATION.	11/6/09	WP	DW
2		ADDED NEW BRG. CUTTER RBSC7048-P FOR BEARING #406-312-100-101 PER E.B.	5/2/11	RJC	
3		CH'D -3 B FROM .312, CORRECTED -11 SCALE TO REFLECT PART REPRESENTATION PER S.E.	6/24/11	RJC	RW
4		-5 CH'D DIM SCHEME, REDREW SECTION VIEW.	7/13/2015	BIM	SE
5	15-0470	UPDATED TO NEW DRAFTING STANDARDS. ADDED NEW BEARING MODELS.	7/13/2015	SM	JAG
6	16-0112	UPDATED TO NEW STANDARD. ADDED CASE RSR GROUP #10137 TO BOM. -1 CH'D MAT'L WAS 1018 IS 1018/1020 CR. CH'D DIMS WAS Ø.625 IS Ø.63, WAS 5/16-24 UNF IS 5/16-24 UNF-2B, ADDED SPEC. -3 CH'D MAT'L WAS 4140 Q&T RND BAR IS 4140/4142. CH'D DIM WAS .032 X 45° IS .03 X 45°. ADDED HEAT TREAT AND SPEC. -5 CH'D DIMS WAS R.030 IS R.03, WAS .015 X 45° IS .02 X 45°, WAS R.015 MAX IS R.02 MAX. ADDED DIM 4X Ø.219 ±.23 EQUALLY SPACED, ADDED SPEC. -11 CH'D MAT'L WAS 4140 Q&T IS 4140/4142. ADDED HEAT TREAT AND SPEC. CH'D DIMS WAS 1/4-20 MACHINE THREADS IS 1/4-20 UNC-2A, WAS 5/16-24 MACHINE THREADS IS 5/16-24 UNF-2A.	8/11/2016	DEW	SM




ASSY QTY	ASSY QTY	B/O	Part #	UNIT QTY	Description	Material	B/O INFORMATION OR SPECIFICATIONS	PG.
			-1	1	SPRING TENSIONER	1018/1020 CR		2
			-3	1	SEAT	4140/4142		3
			-5	1	CUTTER	O-1		4
			-7	1	GUIDE	BRONZE		5
			-9	1	BUSHING	BRONZE		6
			-11	1	STUD	4140/4142		7
		B/O	-15	1	SPIRAL EXTERNAL RETAINING RING	STEEL	Ø7/16 SHAFT (MCMaster-CARR # 91665A350)	1
		B/O	-17	1	THRUST BEARING	STEEL	Ø 5/8 ID. X 1-1/8 OD. X 5/64 (APPLIED # NTA-1018)	1
		B/O	-19	2	THRUST WASHER	STEEL	Ø 5/8 ID. X 1-1/8 OD. X 1/16 (APPLIED # TRB-1018)	1
		B/O	-23	1	FIXED PIN SPANNER WRENCH	STEEL	Ø 1-1/4 OD. X Ø 13/64 PIN (MCMaster-CARR # 5475A12)	1
		B/O	-25	1	CREST TO CREST SPRING	STEEL	SMALLEY CO. # CS112-H2	1
		B/O	-27	1	ROTATING FLANGE NUT	STEEL	1/4-20 ROTATING FLANGE NUT (MCMaster-CARR #90477A029)	1
		B/O	-29	1	TOOTH GUARD (FOR SHIPPING ONLY)	VINYL	SEE -5 ØB PAGE 4 FOR INSIDE DIA, OF TUBE X 5/8 LENGTH	1
		B/O	-31	1	CASE	PLASTIC	(RSR GROUP # 10137)	N/S


DART AEROSPACE	
TITLE RBSC7###-P SERIES PORTABLE BEARING CUTTERS FOR BELL BEARINGS	
DWG NO. RBSC7###-P	REV 6
MAT'L	UNLESS OTHERWISE SPECIFIED
HEAT TREAT	DIMENSIONS ARE IN INCHES
FINISH	.XXX ± .005 FRACTIONS ± 1/8
SPEC	.XX ± .01 ANGLES ± 5°
	.X ± .1 SURFACES = 125/✓
DRAWN BY: MACKOVJAK	1. BREAK ALL SHARP EDGES
CHECKED: DUERFELDT	.015 x 45° OR .015R
OPPS APPR: ANDERSON	2. DIMENSIONAL LIMITS APPLY AFTER PLATING
QA APPR: LINDSAY	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
APPROVED: GILBERT	USED ON MODEL
SCALE 1:2	DATE 7/13/2015
SHEET 1 OF 7	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1		CH'D TOOL # RBSC412-010-182-103-P TO RBSC7188 TO CLARIFY TOOLING IDENTIFICATION.	11/6/09	WP	DW
2		ADDED NEW BRG. CUTTER RBSC7048-P FOR BEARING # 406-312-100-101 PER E.B.	5/2/11	RJC	
6	16-0112	-1 CH'D MAT'L WAS 1018 IS 1018/1020 CR. CH'D DIMS WAS $\varnothing .625$ IS $\varnothing .63$, WAS 5/16-24 UNF IS 5/16-24 UNF-2B. ADDED SPEC.	8/11/2016	DEW	SM



SECTION A-A






(1)

SPRING TENSIONER

DART AEROSPACE	
TITLE RBSC7###-P SERIES PORTABLE BEARING CUTTERS FOR BELL BEARINGS	
DWG NO. RBSC7###-P-1	REV 6
MAT'L 1018/1020 CR	UNLESS OTHERWISE SPECIFIED
HEAT TREAT	DIMENSIONS ARE IN INCHES
FINISH BLACK OXIDE	.XXX ± .005 FRACTIONS ± 1/8
SPEC QMSI-6.2.2, B.O. REV D	.XX ± .01 ANGLES ± 5°
DRAWN BY: MACKOVJAK	.X ± .1 SURFACES = 125°
CHECKED: DUERFELDT	1. BREAK ALL SHARP EDGES
OPPS APPR: ANDERSON	.015 x 45° OR .015R
QA APPR: LINDSAY	2. DIMENSIONAL LIMITS APPLY
APPROVED: GILBERT	AFTER PLATING
SCALE 1:1	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
DATE 7/9/2015	USED ON MODEL
SHEET 2 OF 7	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1		CHANGED TOOL#RBSC412-010-182-103-P TO CLARIFY TOOLING IDENTIFICATION.	11/6/09	WP	DW
2		ADDED NEW BRG. CUTTER RBSC7048-P FOR BEARING #406-312-100-101 PER E.B.	5/2/11	RJC	
3		CH'D -3 B FROM 3.12 PER S.E.	6/24/11	RJC	RW
6	16-0112	-3 CH'D MAT'L WAS 4140 Q&T RND BAR IS 4140/4142. CH'D DIM WAS .032 X 45° IS .03 X 45°. ADDED HEAT TREAT AND SPEC.	8/11/2016	DEW	SM




TOOL NUMBER	ØA +.002 -.000	ØB +.002 -.000	C +.010 -.010	D +.010 -.010	ØE +.000 -.002	F +.5 -.0
RBSC7008-P	.968	.250	.750	.375	1.250	64.5
RBSC7028-P	.837	.250	.750	.320	1.125	64.5
RBSC7048-P	1.000	.250	.750	.237	1.125	90
RBSC7188-P	1.063	.250	.750	.375	1.500	64.5

(-3)
SEAT

DART AEROSPACE	
TITLE RBSC7###-P SERIES PORTABLE BEARING CUTTERS FOR BELL BEARINGS	
DWG NO.	REV 6
RBSC7###-P-3	
MAT'L 4140/4142	UNLESS OTHERWISE SPECIFIED
HEAT TREAT RC 28-32	DIMENSIONS ARE IN INCHES
FINISH BLACK OXIDE	.XXX ± .005 FRACTIONS ± 1/8
SPEC QMSI-6.2.2, B.O. REV D	.XX ± .01 ANGLES ± 5°
	.X ± .1 SURFACES = 125
DRAWN BY: MACKOVJAK	1. BREAK ALL SHARP EDGES
CHECKED: DUERFELDT	.015 x 45° OR .015R
OPPS APPR: ANDERSON	2. DIMENSIONAL LIMITS APPLY
QA APPR: LINDSAY	AFTER PLATING
APPROVED: GILBERT	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
SCALE 2:1	DATE 7/9/2015
	SHEET 3 OF 7

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1		CHANGED TOOL # RBSC412-010-182-103-P TO RBSC7188-P TO CLARIFY TOOLING IDENTIFICATION.	11/6/09	WP	DW
2		ADDED NEW BRG. CUTTER RBSC7048-P FOR BEARING #406-312-100-101 PER E.B.	5/2/11	RJC	
4		-5 CH'D DIM SCHEME, REDREW SECTION VIEW.	1/7/13	BIM	SE
6	16-0112	-5 CH'D DIMS WAS R.030 IS R.03, WAS .015 X 45° IS .02 X 45°, WAS R.015 MAX IS R.02 MAX. ADDED DIM 4X Ø.219 ∇ .23 EQUALLY SPACED. ADDED SPEC.	8/11/2016	DEW	SM



SECTION C-C

DETAIL M
SCALE 3 : 1




TOOL NUMBER	Ø A +.000 -.010	Ø B +.000 -.002	Ø C +.000 -.005	D REF.	E +.010 -.010	F TOOTH AMT.	G
RBSC7008-P	1.375	1.0185	.899	.220	1.187	8	.578
RBSC7028-P	1.375	.927	.807	.220	1.187	8	.578
RBSC7048-P	1.500	1.115	.995	.220	1.187	10	.578
RBSC7188-P	1.500	1.115	.995	.220	1.187	10	.578

(-5)
CUTTER

DART AEROSPACE			
TITLE RBSC7###-P SERIES PORTABLE BEARING CUTTERS FOR BELL BEARINGS			
DWG NO. RBSC7###-P-5			REV 6
MAT'L O-1		UNLESS OTHERWISE SPECIFIED	
HEAT TREAT RC 55-60		DIMENSIONS ARE IN INCHES	
FINISH BLACK OXIDE		.XXX \pm .005 FRACTIONS \pm 1/8	
SPEC QMSI-6.2.2, B.O. REV D		.XX \pm .01 ANGLES \pm 5°	
DRAWN BY: MACKOVJAK		.X \pm .1 SURFACES = 125✓	
CHECKED: DUERFELDT		1. BREAK ALL SHARP EDGES	
OPPS APPR: ANDERSON		.015 x 45° OR .015R	
QA APPR: LINDSAY		2. DIMENSIONAL LIMITS APPLY	
APPROVED: GILBERT		AFTER PLATING	
SCALE 3:2		3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009	
DATE 7/13/2015		USED ON MODEL	
SHEET 4 OF 7			

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1		CH'D TOOL # RBSC412-010-182-103-P TO RBSC7188-P TO CLARIFY TOOLING IDENTIFICATION	11/6/09	WP	DW
2		ADDED NEW BRG. CUTTER RBSC7048-P FOR BEARING #406-312-100-101 PER E.B.	5/2/11	RJC	






(-7)

GUIDE

DART AEROSPACE																					
TITLE RBSC7###-P SERIES PORTABLE BEARING CUTTERS FOR BELL BEARINGS																					
DWG NO. RBSC7###-P-7	REV 6																				
<table border="1"> <tr> <td>MAT'L BRONZE</td> <td>UNLESS OTHERWISE SPECIFIED</td> </tr> <tr> <td>HEAT TREAT</td> <td>DIMENSIONS ARE IN INCHES</td> </tr> <tr> <td>FINISH</td> <td>.XXX \pm .005 FRACTIONS \pm 1/8</td> </tr> <tr> <td>SPEC</td> <td>.XX \pm .01 ANGLES \pm 5°</td> </tr> <tr> <td></td> <td>.X \pm .1 SURFACES = 125 \checkmark</td> </tr> <tr> <td>DRAWN BY: MACKOVJAK</td> <td>1. BREAK ALL SHARP EDGES</td> </tr> <tr> <td>CHECKED: DUERFELDT</td> <td>.015 x 45° OR .015R</td> </tr> <tr> <td>OPPS APPR: ANDERSON</td> <td>2. DIMENSIONAL LIMITS APPLY AFTER PLATING</td> </tr> <tr> <td>QA APPR: LINDSAY</td> <td>3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009</td> </tr> <tr> <td>APPROVED: GILBERT</td> <td>USED ON MODEL</td> </tr> </table>		MAT'L BRONZE	UNLESS OTHERWISE SPECIFIED	HEAT TREAT	DIMENSIONS ARE IN INCHES	FINISH	.XXX \pm .005 FRACTIONS \pm 1/8	SPEC	.XX \pm .01 ANGLES \pm 5°		.X \pm .1 SURFACES = 125 \checkmark	DRAWN BY: MACKOVJAK	1. BREAK ALL SHARP EDGES	CHECKED: DUERFELDT	.015 x 45° OR .015R	OPPS APPR: ANDERSON	2. DIMENSIONAL LIMITS APPLY AFTER PLATING	QA APPR: LINDSAY	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009	APPROVED: GILBERT	USED ON MODEL
MAT'L BRONZE	UNLESS OTHERWISE SPECIFIED																				
HEAT TREAT	DIMENSIONS ARE IN INCHES																				
FINISH	.XXX \pm .005 FRACTIONS \pm 1/8																				
SPEC	.XX \pm .01 ANGLES \pm 5°																				
	.X \pm .1 SURFACES = 125 \checkmark																				
DRAWN BY: MACKOVJAK	1. BREAK ALL SHARP EDGES																				
CHECKED: DUERFELDT	.015 x 45° OR .015R																				
OPPS APPR: ANDERSON	2. DIMENSIONAL LIMITS APPLY AFTER PLATING																				
QA APPR: LINDSAY	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009																				
APPROVED: GILBERT	USED ON MODEL																				
SCALE 2:1	DATE 7/10/2015 SHEET 5 OF 7																				

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1		CH'D TOOL # RBSC412-010-182-103-P TO RBSC7188-P TO CLARIFY TOOLING IDENTIFICATION	11/6/09	WP	DW
2		ADDED NEW BRG. CUTTER RBSC7048-P FOR BEARING #406-312-100-101 PER E.B.	5/2/11	RJC	





-9

BUSHING

DART AEROSPACE											
TITLE RBSC7###-P SERIES PORTABLE BEARING CUTTERS FOR BELL BEARINGS											
DWG NO. RBSC7###-P-9	REV 6										
<table border="0"> <tr> <td>MAT'L BRONZE</td> <td>UNLESS OTHERWISE SPECIFIED</td> </tr> <tr> <td>HEAT TREAT</td> <td>DIMENSIONS ARE IN INCHES</td> </tr> <tr> <td>FINISH</td> <td>.XXX ± .005 FRACTIONS ± 1/8</td> </tr> <tr> <td>SPEC</td> <td>.XX ± .01 ANGLES ± 5°</td> </tr> <tr> <td></td> <td>.X ± .1 SURFACES = 125°</td> </tr> </table>		MAT'L BRONZE	UNLESS OTHERWISE SPECIFIED	HEAT TREAT	DIMENSIONS ARE IN INCHES	FINISH	.XXX ± .005 FRACTIONS ± 1/8	SPEC	.XX ± .01 ANGLES ± 5°		.X ± .1 SURFACES = 125°
MAT'L BRONZE	UNLESS OTHERWISE SPECIFIED										
HEAT TREAT	DIMENSIONS ARE IN INCHES										
FINISH	.XXX ± .005 FRACTIONS ± 1/8										
SPEC	.XX ± .01 ANGLES ± 5°										
	.X ± .1 SURFACES = 125°										
<table border="0"> <tr> <td>DRAWN BY: MACKOVJAK</td> <td>1. BREAK ALL SHARP EDGES</td> </tr> <tr> <td>CHECKED: DUERFELDT</td> <td>.015 x 45° OR .015R</td> </tr> <tr> <td>OPPS APPR: ANDERSON</td> <td>2. DIMENSIONAL LIMITS APPLY</td> </tr> <tr> <td>QA APPR: LINDSAY</td> <td>AFTER PLATING</td> </tr> <tr> <td>APPROVED: GILBERT</td> <td>3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009</td> </tr> </table>		DRAWN BY: MACKOVJAK	1. BREAK ALL SHARP EDGES	CHECKED: DUERFELDT	.015 x 45° OR .015R	OPPS APPR: ANDERSON	2. DIMENSIONAL LIMITS APPLY	QA APPR: LINDSAY	AFTER PLATING	APPROVED: GILBERT	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
DRAWN BY: MACKOVJAK	1. BREAK ALL SHARP EDGES										
CHECKED: DUERFELDT	.015 x 45° OR .015R										
OPPS APPR: ANDERSON	2. DIMENSIONAL LIMITS APPLY										
QA APPR: LINDSAY	AFTER PLATING										
APPROVED: GILBERT	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009										
USED ON MODEL											
SCALE 2:1	DATE 7/10/2015 SHEET 6 OF 7										

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.


REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1		CH'D TOOL # RBSC412-010-182-103-P TO RBSC7188-P TO CLARIFY TOOLING IDENTIFICATION.	11/6/09	WP	DW
2		ADDED NEW BRG. CUTTER RBSC7048-P FOR BEARING #406-312-100-101 PER E.B.	5/2/11	RJC	
3		CORRECTED -11 SCALE TO REFLECT PART REPRESENTATION PER S.E.	6/24/11	RJC	RW
6	16-0112	-11 CH'D MAT'L WAS 4140 Q&T IS 4140/4142. ADDED HEAT TREAT AND SPEC. CH'D DIMS WAS 1/4-20 MACHINE THREADS IS 1/4-20 UNC-2A, WAS 5/16-24 MACHINE THREADS IS 5/16-24 UNF-2A.	8/11/2016	DEW	SM



TOOL NUMBER	$\begin{array}{c} \phi A \\ +.000 \\ -.002 \end{array}$	B	$\begin{array}{c} C \\ +.000 \\ -.020 \end{array}$	$\begin{array}{c} D \\ +.020 \\ -.010 \end{array}$	$\begin{array}{c} E \\ +.000 \\ -.002 \end{array}$	ϕF
RBSC7008-P	.310	1/4-20 UNC	.750	3.875	.250	.500
RBSC7028-P	.310	1/4-20 UNC	.750	3.812	.250	.500
RBSC7048-P	.373	1/4-20 UNC	.680	4.000	.250	.500
RBSC7188-P	.310	1/4-20 UNC	.680	3.875	.250	.500

(-11)

STUD

			
TITLE RBSC7###-P SERIES PORTABLE BEARING CUTTERS FOR BELL BEARINGS			
DWG NO. RBSC7###-P-11			REV 6
MAT'L 4140/4142		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	
HEAT TREAT RC 28-32		.XXX ± .005 FRACTIONS ± 1/8	
FINISH BLACK OXIDE		.XX ± .01 ANGLES ± 5°	
SPEC QMSI-6.2.2, B.O. REV D		.X ± .1 SURFACES = 125/√	
DRAWN BY: MACKOVJAK		1. BREAK ALL SHARP EDGES .015 x 45° OR .01SR	
CHECKED: DUERFELDT		2. DIMENSIONAL LIMITS APPLY AFTER PLATING	
OPPS APPR: ANDERSON		3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009	
QA APPR: LINDSAY		USE ON MODEL	
APPROVED: GILBERT			
SCALE 1:1		DATE 7/13/2015	
SHEET 7 OF 7			